

TOTEM

Discover yours

- A WORLD OF QUALITY SOLUTIONS -

- New Architectural Solutions -

• NEW KIN IC6 ULTRA SLIM



Model: KIN IC6 ULTRA SLIM - 6 Inch In-Ceiling

Frequency Response: **55Hz - 25kHz**Recommended Power: **25 - 100 W**

Impedence: **8 ohm** Efficency: **90 dB**

Dimensions: diameter 9.29 in x depth 2.05 in

diameter 236 mm x depth 52 mm Cut Out: diameter 8.15 in/207 mm



Pre Construction Bracket

Model: KIN IC-PCK6US



KIN IW SLIM SERIES



Model: KIN IW**6 SLIM - 6 Inch In-Wall**Frequency Response: **55Hz - 25kHz**Recommended Power: **10 - 100 W**

Impedence: **8 ohm** Efficency: **90 dB**

Dimensions:(W/H/D):**8.97 x 12.4 x 3.5 in/**

229 x 315 x 89 mm

Cut Out: 7.48 x 10.71 in/190 x 277 mm



Model: KIN IW8 SLIM - 8 Inch In Wall Frequency Response: 48Hz - 25kHz Recommended Power: 10 - 125 W

Impedence: 8 ohm
Efficency: 91 dB

Dimensions: (W/H/D):10.39 x 14.33 x 3.89 in

 $264 \times 364 \times 102 \ mm$

Cut Out: 8.85 x 12.75 in/225 x 328mm

KIN IW PCB6-Pre Construction Brackets

KIN IW PCB8-Pre Construction Brackets

NEW KIN IW6C SLIM

Designed to adapt to various configurations. It shines as an LCR (Left-Center-Right) setup, delivering balanced audio projection. Moreover, it seamlessly expands its capabilitises to complement the KIN IW6 and KIN IW8 models!



Model: KIN IW6C SLIM - 6 Inch In Wall Frequency Response: 50 Hz - 20kHz Recommended Power: 20 - 125 W


Impedence: **8 ohm** Efficency: **91 dB**

Dimensions: (W/H/D):16 x 9.21 x 3.54 in/

408 x 234 x 90mm

Cut Out: 14.56 x 7.71 in/ 370 x 196 mm

KIN IC SERIES



KIN IC62SST

Design: 6.5 Inch In-Ceiling

Frequency Response: **50Hz - 30kHz**Recommended Power: **20 - 90 W**

Impedence: 8 ohm Efficency: 90 dB

Dimensions: diameter 9.2 x depth 4 in diameter 245 x depth 119 mm

Cut Out: diameter 8.3 in/213 mm

Dual Mode:

Experience the best of both worlds with our versatile KIN IC62 SST. Switch effortlessly between surround sound for an immersive cinematic experience and single stereo mode in smaller confined spaces where multiple loudspeakers are not possible.

Optional Black Grills Now Available!



KIN IC6

Design: 6.5 Inch In-Ceiling

Frequency Response: **50Hz - 30kHz**Recommended Power: **20 - 90 W**

Impedence: 8 ohm Efficency: 90 dB

Dimensions: diameter 9.2 x depth 4 in

diameter 245 x depth 119 mm Cut ○ut: diameter 8.3 in/213 mm



KIN IC62

Design: 6.5 Inch In-Ceiling

Frequency Response: **46Hz - 30kHz**Recommended Power: **20 - 110 W**

Impedence: 8 ohm Efficency: 90 dB

Dimensions: diameter 9.65 x depth 4.7 in
diameter 245 mm x depth 119 mm
Cut Out: diameter 8.3 in/213 mm



KIN IC SERIES

ACCESSORIES



PCK6 and PCK8 Pre-Construction Kits are color coded to helpfully indicate proper speaker size to ensure installation efficiency and prevent time consuming, costly mistakes. Multiple points to connect the wings guarantee that contact with drywall is always within access. Wings have convenient measurement indications. Each rigid frame is equipped with a joist bracket that allows all speakers to be installed in a perfect line simply and flawlessly. Available by unit or master pack. Sound isolating ABC6, ABC6SST, and ABC8 Acoustic Back Cans connect quickly, simply, and can reduce sound from penetrating adjacent rooms by 24dB. Neodymium magnets ensure a snug fit but screw holes at the extremities of each corner allow the frame to be tightened to the drywall and eliminate any gaps. Stainless steel resists corrosion, micro-perforation grille for the most uniform color, and paintable with an easily removable and replaceable scrim cloth.

Acoustic Back Cans

Model: KIN IC-ABC6
FOR Models: KIN IC 62

Model: KIN IC-ABC62SST FOR Models: KIN IC 62SST

Model: KIN IC-ABC8
FOR Models: KIN IC 82





Square Grill KIT

Model: KIN IC-SGK6 For: KIN IC 6 /62 / SST

Model: KIN IC-SGK8
For: KIN IC 8-KIN IC82



Pre Construction Brackets

Red Model: KIN IC-PCK6

FOR Models: KIN IC6/62 / 62SST

Model MASTER PACK: 10 kits

Green Model: KIN IC-PCK8 FOR Models: KIN IC 8/82

Model MASTER PACK: 10 kits

KIN AIC KIN LCR KIN IW

Designed and engineered with you in mind!

Full back-boxed, high-performance In-Ceiling/In-Wall loudspeaker



Model: KIN AIC DIMS: 14.09 x 14.09 x 4.72 in

358 x 358 x 120 mm Cut-Out:13.38 x 13.38 in (340 x 340 mm)



Model: KIN LCR

DIMS: 7.09 x 25.51 x 3.75 in

180 x 648 x 95.25 mm Cut-Out: 6.37 x 24.8 in (161.8 x 630 mm)

TRIBE-KIN PCB AIC - Pre Construction Bracket

Model: KIN IW

DIMS:15.27 x 7.09 x 3.75 in

388 x 188 x 95.25 mm
Cut-Out:14..56 x 6.37 in 370 x161.8 mm

TRIBE-KIN PCB AIC - Pre Construction Brackets



TRIBE-KIN PCB IW
Pre Construction Brackets

SPECIFICATIONS

OPTIONAL BLACK GRILLS NOW AVAILABLE

KIN AIC Frequency Response: $59 \text{ Hz} - 25 \text{ kHz} \pm 3 \text{ dB}$ KIN LCR Frequency Response: $60 \text{ Hz} - 25 \text{ kHz} \pm 3 \text{ dB}$ KIN IW Frequency Response: $69 \text{ Hz} - 25 \text{ kHz} \pm 3 \text{ dB}$

Recommended Power: 30 - 120 W

Woofer: Twin MHEX phenolic honeycomb woven hybrid woofer in die-cast basket

Passive radiators: Dual 5" metal amalgamation compound

Tweeter: 1"/2.54cm Titanium infused soft dome

Impedance: 6 ohms / Sensitivity dB @IW-IM: 90-91 dB Grill Type: Magnetic, paintable, virtually bezel-less white metal

Speaker Terminals: 5-way gold plated terminals

TRIBE AIC - TRIBE LCR - TRIBE IW

Assembled in house by our skilled production team!

Full back-boxed, high-performance In-Ceiling/In-Wall loudspeaker Made in Canada *

Model: TRIBE IW - Sealed In-Wall

Frequency Response: 60 Hz - 30 kHz ± 3 dB

Recommended Power: 30 - 140 W

Impedence: 6 ohm Sensitivity: 90dB

DIMS: 15.27 x 7.09 x 3.75 in/388 x 188 x 95.25 mm

Cut-Out: 14.56 x 6.37 in/370 x 161.8 mm



TRIBE-KIN PCB IW - Pre Construction Bracket:



Model: TRIBE AIC - Sealed Angled In-Ceiling Frequency Response: 47 Hz - 30 kH z ± 3 dB

Recommended Power: 30 - 140 W

Impedence: 6 ohm Sensitivity: 91 dB

DIMS: 14.09 x 14.09 x 6.125 in/358 x 358 x 155 mm

Cut-Out: 13.38 x 13.38 in/340 x 340mm

TRIBE-KIN PCB AIC - Pre Construction Bracket:

Model: TRIBE LCR - Sealed In-Wall

Frequency Response: 50 Hz - 30 kH z ± 3 dB

Recommended Power: 30 - 140 W

Impedence: 6 ohm Sensitivity: 90 dB

DIMS: 7.09 x 25.51 x 3.75/180 x 648 x 95.25 mm

Cut-Out: 6.37 x 24.8 in / 161.8x 630 mm

TRIBE-KIN PCB LCR - Pre Construction Bracket:

OPTIONAL BLACK GRILLS NOW AVAILABLE

Grill Type: Magnetic, Paintable, virtually bezel-less white metal

Accessories: Pre-Construction Brackets

Speaker Terminals: 2 sets of 5-way gold plated binding posts



TRIBE INWALL / ONWALL SUBWOOFERS

Model: TRIBE SOLUTION SUB

Frequency Response: 26Hz - 200kHz

Powered: **500W Amplifier**

Dimensions: 24.01 x 13.07 x 4.52

/610 x 332 x 115 mm

Magnetic Grill, Adhesive Feet, Power Cord & Two Stands Included!



Consider going wireless with the NEW LINK Wireless Transmitter!



Model: **TRIBE IN WALL DOUBLE 8 SUB**Frequency Response: **26Hz - 200kHz**Powered: **500W Outboard Amplifier**

Amplifier: Can Power two Double 8 Modules Dimensions: $(W/H/D):14.44 \times 23.5 \times 3.78 \text{ in } /$

(W/H/D):365.76 x 596.90 x 96.01 mm

Cut Out: (W/H) 12.4 x 22.4 in/314.96 X 568.96 mm

Extra Sub Module

Rack Ears & Magnetic Paintable Grill Included!

Model: TRIBE IN WALL SUB 12

Frequency Response: 22Hz - 200kHz
Powered: 500W Outboard Amplifier
Dimensions (W/H/D):16.85 x 28.27 x 3.78 in

(W/H/D):427.99 x 718.06 x 96.01 mm

Cut Out: (W/H) 14.57 x 27.16 in/270.01 X 96.01 mm



• TRIBE SOLUTION BARS

- MADE IN CANADA -



Made in Canada *

TRIBE DUO SOLUTION BAR

Sized for 65 inch & larger TV **Satin Black, Satin White**

Frequency Response: 65Hz - 25kHz Recommended Power: 20 - 120 W

Impedence: 8 ohm Sensitivity: 90dB

DIMS: 57W 6.18H 3.54D /

144.8 x 15.7 x 9cm

TRIBE TRIO SOLUTION BAR

Sized for 65 inch & larger TV **Satin Black, Satin White**

Frequency Response: 55Hz - 25kHz Recommended Power: 20 - 150 W

Impedence: 8 ohm Sensitivity: 90dB

DIMS: 57W 6.18H 3.54D /

144.8 x 15.7 x 9cm

Magnetic Grill and Wall Bracket Included!

Magnetic Grill and Wall Bracket Included!



TRIBE III

Satin Black, Satin White & Silver



Frequency Response: 40Hz - 25kHz Recommended Power: 30 - 200 W

Impedence: 4 ohm Sensitivity: 89dB

DIMS: **DIMS: 5.91W 36H 3.75D**

Magnetic Grill and Wall Bracket Included!



TRIBE III DESIGN

DUSK or ICE - FIRE ON ORDER

Frequency Response: 40Hz - 25kHz Recommended Power: 30 - 200 W

Impedence: 4 ohm Sensitivity: 89dB

DIMS: **DIMS: 5.91W 36H 3.5D**

TRIBE V

Satin Black, Satin White & Silver

Frequency Response: 34Hz - 25kHz Recommended Power: 30 - 200 W

Impedence: 8 ohm Sensitivity: 89dB

DIMS: 6.25W 48H 3.75D

TRIBE V DESIGN DUSK or ICE - FIRE ON ORDER

Frequency Response: 34Hz - 25kHz Recommended Power: 30 - 200 W

Impedence: 8 ohm Sensitivity: 89dB

DIMS: 6.18W 48H 3.5D

Magnetic Grill and Wall Bracket Included!









www.allegra-acoustic-art.swiss

Allegra Acoustic Art GmbH Chrobüelstrasse 2 CH 9602 Bazenheid info@allegra-acoustic-art.swiss



september 2025